Listing of the Claims

1. (Currently Amended)   A method for monitoring a system in which a datum-line display is generated on a viewing screen for at least one parameter of the system as follows:

-                logging of a variation with time of the values of the parameter concerned,

-                determination of a base value for the parameter concerned,

-                determination of an instantaneous deviation between the base value and the current parameter value or a current mean value of a specified group, containing the current parameter value, of consecutive parameter values,

-                creation of a baseline representing the base value,

-                display of the baseline on the viewing screen in such a way that the baseline extends horizontally on the viewing screen and with a specified length,

-                creation of a continuous curve that represents the variation with time of the parameter values for a specified time period and is normalized with respect to the baseline,

-                display of the continuous curve on the viewing screen in such a way that ~~its~~ the continuous curve's time axis extends horizontally on the viewing screen and that the continuous curve on the viewing screen essentially extends over the entire length of the baseline,

-                creation of a deviation bar that represents the instantaneous deviation and is normalized with respect to the baseline,

-                display of the deviation bar on the viewing screen in such a way that ~~it~~ the deviation bar extends vertically on the viewing screen from the level of the baseline, wherein the datum-line display has a trend arrow that is generated as follows:

-                determination of the trend of the value variation with time in the current parameter value,

-                creation of the trend arrow, which represents the trend,

-                display of the trend arrow on the viewing screen and wherein the trend arrow is displayed on the viewing screen in such a way that the trend arrow points upward in the case of a positive instantaneous slope and points downward in the case of a negative instantaneous slope.

.

2. (Canceled) A method as claimed in claim 1, wherein the datum-line display has a trend arrow that is generated as follows:

- determination of the trend of the value variation with time in the current parameter value,

- creation of the trend arrow, which represents the trend,

- display of the trend arrow on the viewing screen.

3. (Currently Amended)   A method as claimed in claim ~~2~~1, wherein the trend arrow is displayed on the viewing screen in such a way that ~~it~~ the trend arrow is disposed adjacently to one end of the continuous curve on the viewing screen.

4. (Canceled) A method as claimed in claim 2, wherein the trend arrow is displayed on the viewing screen in such a way that it points upward in the case of a positive instantaneous slope and points downward in the case of a negative instantaneous slope.

5. (Currently Amended)   ~~A method as claimed in claim 2,~~ A method for monitoring a system in which a datum-line display is generated on a viewing screen for at least one parameter of the system as follows:

- logging of a variation with time of the values of the parameter concerned,

- determination of a base value for the parameter concerned,

- determination of an instantaneous deviation between the base value and the current parameter value or a current mean value of a specified group, containing the current parameter value, of consecutive parameter values,

- creation of a baseline representing the base value,

- display of the baseline on the viewing screen in such a way that the baseline extends horizontally on the viewing screen and with a specified length,

- creation of a continuous curve that represents the variation with time of the parameter values for a specified time period and is normalized with respect to the baseline,

- display of the continuous curve on the viewing screen in such a way that the continuous curve's time axis extends horizontally on the viewing screen and that the continuous curve on the viewing screen essentially extends over the entire length of the baseline,

- creation of a deviation bar that represents the instantaneous deviation and is normalized with respect to the baseline,

- display of the deviation bar on the viewing screen in such a way that the deviation bar extends vertically on the viewing screen from the level of the baseline, wherein the datum-line display has a trend arrow that is generated as follows:

- determination of the trend of the value variation with time in the current parameter value,

- creation of the trend arrow, which represents the trend,

- display of the trend arrow on the viewing screen and wherein the orientation of the trend arrow depends on the value of the instantaneous slope.

6. (Currently Amended)   A method as claimed in claim ~~2~~1, wherein the trend arrow is disposed between the continuous curve and the deviation bar on the viewing screen, or in that the trend arrow is disposed on the viewing screen in such a way that the deviation bar is situated between the trend arrow and the continuous curve.

7. (Currently Amended)   ~~A method as claimed in claim 2,~~ A method for monitoring a system in which a datum-line display is generated on a viewing screen for at least one parameter of the system as follows:

- logging of a variation with time of the values of the parameter concerned,

- determination of a base value for the parameter concerned,

- determination of an instantaneous deviation between the base value and the current parameter value or a current mean value of a specified group, containing the current parameter value, of consecutive parameter values,

- creation of a baseline representing the base value,

- display of the baseline on the viewing screen in such a way that the baseline extends horizontally on the viewing screen and with a specified length,

- creation of a continuous curve that represents the variation with time of the parameter values for a specified time period and is normalized with respect to the baseline,

- display of the continuous curve on the viewing screen in such a way that the continuous curve's time axis extends horizontally on the viewing screen and that the continuous curve on the viewing screen essentially extends over the entire length of the

baseline,

- creation of a deviation bar that represents the instantaneous deviation and is normalized with respect to the baseline,

- display of the deviation bar on the viewing screen in such a way that the deviation bar extends vertically on the viewing screen from the level of the baseline, wherein the datum-line display has a trend arrow that is generated as follows:

- determination of the trend of the value variation with time in the current parameter value,

- creation of the trend arrow, which represents the trend,

- display of the trend arrow on the viewing screen and wherein the trend arrow points in the vertical direction at one end of the continuous curve if the instantaneous slope has the value zero or is in a specified interval containing the value zero.

8. (Currently Amended) ~~A method as claimed in claim 1,~~ A method for monitoring a system in which a datum-line display is generated on a viewing screen for at least one parameter of the system as follows:

- logging of a variation with time of the values of the parameter concerned,

- determination of a base value for the parameter concerned,

- determination of an instantaneous deviation between the base value and the current parameter value or a current mean value of a specified group, containing the current parameter value, of consecutive parameter values,

- creation of a baseline representing the base value,

- display of the baseline on the viewing screen in such a way that the baseline extends horizontally on the viewing screen and with a specified length,

- creation of a continuous curve that represents the variation with time of the parameter values for a specified time period and is normalized with respect to the baseline,

- display of the continuous curve on the viewing screen in such a way that the continuous curve's time axis extends horizontally on the viewing screen and that the continuous curve on the viewing screen essentially extends over the entire length of the baseline,

- creation of a deviation bar that represents the instantaneous deviation and is

normalized with respect to the baseline,

- display of the deviation bar on the viewing screen in such a way that the deviation bar extends vertically on the viewing screen from the level of the baseline and wherein the display of the continuous curve can be deactivated.

9. (Currently Amended) ~~A method as claimed in claim 1,~~ A method for monitoring a system in which a datum-line display is generated on a viewing screen for at least one parameter of the system as follows:

- logging of a variation with time of the values of the parameter concerned,

- determination of a base value for the parameter concerned,

- determination of an instantaneous deviation between the base value and the current parameter value or a current mean value of a specified group, containing the current parameter value, of consecutive parameter values,

- creation of a baseline representing the base value,

- display of the baseline on the viewing screen in such a way that the baseline extends horizontally on the viewing screen and with a specified length,

- creation of a continuous curve that represents the variation with time of the parameter values for a specified time period and is normalized with respect to the baseline,

- display of the continuous curve on the viewing screen in such a way that the continuous curve's time axis extends horizontally on the viewing screen and that the continuous curve on the viewing screen essentially extends over the entire length of the baseline,

- creation of a deviation bar that represents the instantaneous deviation and is normalized with respect to the baseline,

- display of the deviation bar on the viewing screen in such a way that the deviation bar extends vertically on the viewing screen from the level of the baseline and wherein the deviation bar extends on the viewing screen adjacently to the more recent end of the continuous curve.

10. (Currently Amended) A method as claimed in claim ~~1~~8,

- wherein the datum-line display has a rectangular window whose top side and bottom side extend parallel to the baseline and have the same geometrical spacing in

PHDE030263US

the vertical direction from the baseline,

-            wherein a specified upper limit value for the parameter concerned is assigned to the top side,

-            wherein a specified lower limit value for the parameter concerned is assigned to the bottom side,

-            wherein the continuous curve and the deviation bar are, in addition, normalized with respect to the upper limit value and the lower limit value.

11. (Previously Presented)   A method as claimed in claim 10,

-            wherein an upper limit-value line representing the upper limit value is created and is displayed on the viewing screen in such a way that it essentially extends over the entire length of the baseline on the top side of the rectangular window,

-            wherein a lower limit-value line representing the lower limit value is created and is displayed on the viewing screen in such a way that it essentially extends over the entire length of the baseline on the bottom side of the rectangular window.

12. (Previously Presented)   A method as claimed in claim 10, wherein the limit values have different numerical spacings from the base value although the top side and the bottom side have the same geometrical spacing from the baseline on the viewing screen.

13. (Currently Amended)   A method as claimed in claim ~~18~~, wherein the continuous curve does not cover the current parameter value, but those parameter values that precede the current parameter value in a specified time period.

14. (Currently Amended)   A method as claimed in claim ~~18~~, wherein a separate datum-line display is generated in each case for a plurality of different parameters in such a way that a plurality of datum-line displays are disposed horizontally next to one another on the viewing screen and in that the baselines of horizontally adjacent datum-line displays are disposed coaxially in alignment with one another on the viewing screen.

15. (Previously Presented)   A method as claimed in claim 10,

-            wherein the top sides of the rectangular windows of horizontally adjacent

datum-line displays are disposed coaxially in alignment with one another on the viewing screen,

- wherein the bottom sides of the rectangular windows of horizontally adjacent datum-line displays are disposed coaxially in alignment with one another on the viewing screen.

16. (Currently Amended) A method as claimed in claim 1̶8̶, wherein at least one parameter can be selected from a plurality of different parameters of the system for which parameter or parameters a datum-line display is generated in each case.

17. (Currently Amended) A method as claimed in claim 1̶8̶, wherein the system to be monitored is a patient.

18. (Currently Amended) A device suitable for performing the method as claimed in claim 1̶8̶.

19. (Canceled)

20. (Canceled)